

## VHCB Lead Based Paint Hazard Reduction Program Contractor Air Sample Data Sheet - Lead

Date: \_\_\_\_\_ Company: \_\_\_\_\_

Supervisor: \_\_\_\_\_ Certification #: \_\_\_\_\_

Job Address: \_\_\_\_\_

VHCB Building #: \_\_\_\_\_ Unit#: \_\_\_\_\_ Age of Building: \_\_\_\_\_

Monitored Employee Name & ID #: \_\_\_\_\_

Pump Type & Serial #									NIOSH 7082 Method 1.0 – 4.0 L / min. air flow 0.8µm cellulose ester membrane 37mm cassette			
Sample Type	Personal		Area		Indoor		Outdoor					
Respirator Type	Half Face w/ HEPA		Full Face w/ HEPA		PAPR	None		Other				
Task 1 Cassette 1	Task 2 Cassette 2		Task 3 Cassette 3			Task 4 Cassette 4						
Engineering Controls Utilized	Engineering Controls Utilized		Engineering Controls Utilized			Engineering Controls Utilized						
Down Time:	Down Time:		Down Time:			Down Time:		Down Time:				
Notes:												
Sample #	Lab #	Time		Flow L/min		Volume Min 200 L Max 1500 L	Results µg/m <sup>3</sup> 8hr TWA					
		Start	Stop	Start	Stop							

Supervisor Signature: \_\_\_\_\_

Date Shipped or Given to VHCB: \_\_\_\_\_ by: \_\_\_\_\_

Date Results Rec'd: \_\_\_\_\_ by: \_\_\_\_\_

Date Reviewed by Monitored Employee: \_\_\_\_\_ Employee Initials: \_\_\_\_\_

(Note: 29 CFR 1926.62 requires employers to notify employees of monitoring results within 5 days of receiving the results.)